

Item	UX-B160WG	
Nozzle Size	65μ m	
Max. print line number	Up to 3 lines	
Maximun number of print characters	Up to 240 characters	
	5x5	✓
	5x7(8), 9x7(8)	✓
	7x10	✓
	10x12	✓
	12x16	✓
	18x24	✓
character height	2-10mm	
Display & input device	WYSIWYG design Input device : Touch panel, input sound provided Display : TFT LCD, Backlight provided. 10.4" Monochrome	
Screen languages	English	
Maximun print late (characters per second) (Font 5x5, space 1, 1line)	Up to 1148	
Standard characters	Alphanumeric(A-Z, a-z, 0-9) symbols(27) and space : Total 90	
User pattern	50patterns each for dot matrix	
Print functions	Calendar, Count, Font mixture, Password	
Message storage capacity	150	
External memory	USB for user data storage	
Head cable length/angle	4m(in-line/90 degrees)	
Operating temperature range	10-45 degree	
Operating humidity range	30-90% RH(no condensation)	
Power supply(Automatic voltage selection)	AC 100-120/220-240±10% 50/60Hz 120VA	
Dimensions(Width x Depth x Height)	400x320x527mm	
international protection	IP55	
Approximate weight	27kg	
Make up consumption(20 degree)	6.0ml/h	
Wiring of power supply	Terminal block	

Main Unit /Printhead Dimension



Note : Main unit dimensions do not include any projections.

Information in this brochure is subject to change without notice.

© Hitachi Industrial Equipment Systems Co., Ltd.

For further information, please contact your nearest sales representative.

© Hitachi Asia Ltd.

(Industrial Components & Equipment Group)

30 Pioneer Crescent #10-15 West Park Bizcentral, Singapore 628560

Tel: (65) 6305 7400 Fax: (65) 6305 7401



Registration number: JQA-QMA12087

Registration date: April 1, 2005

The Marking Systems and Holst Systems Division (Taga Division) of Hitachi Industrial Equipment Systems Co., Ltd. obtained international standard ISO 9001 certification for the quality assurance of the Ink Jet Printer contained in this brochure.

HITACHI
Inspire the Next

Ink Jet Printer **UX-B 160WG**

